



## 9622 — 9722 Stainless Steel Chemical Pumps PTO Shaft and Hydraulic Driven



9622HBFRV

### Typical Applications

- Chemical and transport applications
- Corrosive liquid transfer

### Primary Features

- 316SS Housing
- 17-4 PH SST Gears / Shafts
- Built-in Relief Valve

<b>9622 / 9722 SERIES SS TRUCK PUMPS WITH 90° PORTS — PTO &amp; HYDRAULIC DRIVEN</b>							
<b>PTO DRIVE SHAFT STAINLESS STEEL TRUCK PUMP</b>							
Part Number	Roper Model	Gallons/ Rev.	Flg Size	PTFE Packing or Mech. Seal	Options	Relief Valve	Approx. Weight
ROP9722HBFRV	9722HBFRV	0.22	3"	MECH SEAL	n/a	BUILT-IN	140
ROP9622HBFRV	9622HBFRV	0.22	3"	PACKING / ORINGS	n/a	BUILT-IN	140
<b>HYDRAULIC DRIVEN STAINLESS STEEL TRUCK PUMPS</b>							
ROP9722BHFRV	9722BHFRV	0.22	3"	MECH SEAL	Pump Only for Hyd. Bracket	BUILT-IN	140
ROP9722BHFRV-CPLG	9722MBHFVR13661	0.22	3"	MECH SEAL	W/ Hyd. Bracket and Coupling	BUILT-IN	155
<b>PLEASE CALL FOR HELP WITH PUMP APPLICATIONS OR OTHER SIZE PUMPS</b>							

<b>Hydraulic Motors For Roper BH Models*</b>						
FOR TRUCK PUMP TYPE	Pump Model #	Max Pump RPM	Hyd Motor Shaft Diam.	Hyd Pump GPM Required	Weight	Motor Part No. / (Type)
All Roper BH Model Sizes 11-17-22	3611 / 4722 9622 / 9722	750	<b>1.00"</b>	17GPM	23	HMOTOR80D1.00 (SAE A 2BOLT)
*NOTE: Small 11-17-22 Roper pumps have a 1" drive shaft; Large 32-43-48 Roper pumps have a 1-1/4" drive shaft. Please contact us if you will be turning your pumps at lower speeds or with products more viscous than gas and diesel.						