



Dixon EZLink™ Armless Cam & Groove

Push-to-connect, low profile, positive locking system and more!



assembled with 6200 series elbow

patent pending

Applications:

- transfer and/or unloading of fuels (gasoline or diesel) from tank truck to storage tanks
- transfer of liquids compatible with the available coupling and gasket materials

Materials:

- couplings and dust caps: A356 aluminum, 316 stainless steel
- coupler tabs and springs: 316 stainless steel
- gaskets: Buna-N, Fluorosilicone (blue in color), or FKM (brown in color)

Features:

- automatic couplers push-to-connect providing a reliable connection
- low profile allows easy connection and disconnection in tight applications
- coupler push tabs can be locked with safety pins and/or zip tie
- compatible with standard cam and groove adapters

Specifications:

- refer to dixonvalve.com for maximum crimp working pressure
- Buna-N gasket temperature range: 5°F to 180°F (-15°C to 82°C)
- Fluorosilicone gasket temperature range: -20°F to 180°F (-29°C to 82°C)
- FKM gasket temperature range: 40°F to 200°F (4°C to 93°C)



Warning: Only use EZLink™ gaskets and tabs for this coupling system. Traditional cam and groove handles and gaskets, or other types of seals are not compatible and will fail.

Type B Coupler x Male NPT

Size	A356 Aluminum Part #	316 Stainless Steel Part #
1½"	EZL150-B-AL	EZL150-B-SS
2"	EZL200-B-AL	EZL200-B-SS
3"	EZL300-B-AL	EZL300-B-SS
4"	EZL400-B-AL	---




Type C Coupler x King Crimp™ Hose Shank

Size	A356 Aluminum Part #	316 Stainless Steel Part #
1½"	<i>EZL150-C-AL</i>	<i>EZL150-C-SS</i>
2"	<i>EZL200-C-AL</i>	<i>EZL200-C-SS</i>
3"	<i>EZL300-C-AL</i>	<i>EZL300-C-SS</i>
4"	<i>EZL400-C-AL</i>	---



Type D Coupler x Female NPT

Size	A356 Aluminum Part #	316 Stainless Steel Part #
1½"	<i>EZL150-D-AL</i>	<i>EZL150-D-SS</i>
2"	<i>EZL200-D-AL</i>	<i>EZL200-D-SS</i>
3"	<i>EZL300-D-AL</i>	<i>EZL300-D-SS</i>
4"	<i>EZL400-D-AL</i>	---



Type DC Dust Caps

Size	A356 Aluminum Part #	316 Stainless Steel Part #
1½"	<i>EZL150-DC-AL</i>	<i>EZL150-DC-SS</i>
2"	<i>EZL200-DC-AL</i>	<i>EZL200-DC-SS</i>
3"	<i>EZL300-DC-AL</i>	<i>EZL300-DC-SS</i>
4"	<i>EZL400-DC-AL</i>	---



Replacement Kits

- kit contains: 2 pins, 2 springs and 2 tabs

Size	Part #
2" 3" and 4"	<i>EZL200RPLKIT</i> <i>EZL300RPLKIT</i>



Replacement Gaskets

Size	Buna-N Part #	Fluorosilicone Part #	FKM Part #
1½"	<i>EZL150-G-BU</i>	<i>EZL150-G-FV</i>	<i>EZL150-G-VI</i>
2"	<i>EZL200-G-BU</i>	<i>EZL200-G-FV</i>	<i>EZL200-G-VI</i>
3"	<i>EZL300-G-BU</i>	<i>EZL300-G-FV</i>	<i>EZL300-G-VI</i>
4"	<i>EZL400-G-BU</i>	<i>EZL400-G-FV</i>	<i>EZL400-G-VI</i>



Safety Clip

- clip is optional

Plated Carbon Steel Part #
<i>EZLCL400</i>

