



## Small Series 3711-17- 22 GHB Mechanical Seal Motor Driven Gear Reduction Pumps



### Typical Applications

- Mix, circulate, and transfer viscous liquids
- Gasoline, asphalt, molasses
- Ink, roofing compounds, oils

### Primary Features

- Precise tolerances for maximum efficiency
- Totally enclosed and running in oil, the reduction gears are made of steel to assure longer life. Antifric-tion bearings are used throughout. Three inter-changeable gear ratios are available in each size.

ROPER SMALL 3711 - 3722 SERIES GEAR REDUCTION PUMPS WITH 90 DEG. FLANGED PORTS; BRONZE BUSHINGS; RELIEF VALVE AND BUNA MECHANICAL SEAL							
Part Number (-Gear Ratio)	Roper Model	Max. HP Allowed	Approx gpm with 1750 rpm Motor (100PSI)	Flg Size	Packing Option	Mech. Seal	Weight
<b>STYLE 37xx WITH BUNA MECHANICAL SEAL</b>							
ROP3711GHBFORV	3711GHBFORV	Pump Less Gear Reduction Unit		2"	na	Buna	95
ROP3711GHBFRV-4.60	3711GHBFRV-4.60	8.5	42 GPM	2"	na	Buna	120
ROP3711GHBFRV-3.94	3711GHBFRV-3.94	10	49 GPM	2"	na	Buna	120
ROP3711GHBFRV-3.20	3711GHBFRV-3.20	10	60 GPM	2"	na	Buna	120
ROP3717GHBFORV	3717GHBFORV	Pump Less Gear Reduction Unit		2"	na	Buna	105
ROP3717GHBFRV-4.60	3717GHBFRV-4.60	8.5	65 GPM	2"	na	Buna	140
ROP3717GHBFRV-3.94	3717GHBFRV-3.94	10	75 GPM	2"	na	Buna	140
ROP3717GHBFRV-3.20	3717GHBFRV-3.20	10	92 GPM	2"	na	Buna	140
ROP3722GHBFORV	3722GHBFORV	Pump Less Gear Reduction Unit		3"	na	Buna	140
ROP3722GHBFRV-4.60	3722GHBFRV-4.60	8.5	84 GPM	3"	na	Buna	170
ROP3722GHBFRV-3.94	3722GHBFRV-3.94	10	98 GPM	3"	na	Buna	170
ROP3722GHBFRV-3.20	3722GHBFRV-3.20	10	120 GPM	3"	na	Buna	170
<b>THESE GHB UNITS CAN BE —</b> <b>BASEPLATE MOUNTED WITH ELECTRIC MOTORS</b> <b>INCORPORATED INTO CUSTOM PUMP / METER CARTS OR STANDS</b> <b>HAVE VARIABLE FREQUENCY DRIVES TO CONTROL MOTOR SPEEDS (FOR HEAVIER OILS, ETC.)</b>  <b>PLEASE CALL FOR HELP WITH PUMP APPLICATIONS OR OTHER SIZE PUMPS</b>							